


BOULTON



VIBRO-ENERGY®

CERAMIC POLISHING Wet & Dry Applications:

STANDARD MACHINE DATA

Model	FM-10E	FM-20E	FM-40E
Working Volume	6.5 cu.ft. 184 litres	13 cu.ft. 368 litres	26 cu.ft. 736 litres
Motor Power	1.15 kW	3.3 kW	4.8 kW
Maximum Work-mass Weight	700 kg	1000 kg	1400 kg
Working Height	38 in. 965 mm	40 in. 1005 mm	40 in. 1005 mm
Bowl Diameter	50 in. 1270 mm	58 in. 1473 mm	75 in. 1905 mm
Annular Width	13.5 in. 343 mm	17.25 in. 438 mm	20.5 in. 521 mm
Maximum Size of Ware	6 in. 152 mm	12 in. 305 mm	14 in. 356 mm
Production Rate - Pieces	1500/hour Flat-ware	2250/hour Flat-ware	3000/hour Flat-ware
Shipping Weight	395 kg	1027 kg	1500 kg

The Boulton Ceramic Polishing Mill provides fast, high volume smoothing and polishing of:

- *Tableware*
- *Ornamental ware*

Industrial ceramics in earthen:

- *Bone China,*
- *Vitreous*
- *Porcelain bodies in the biscuit state.*